


POS MV™

WAVEMASTER II SPECIFICATIONS

MAXIMIZE YOUR ROI WITH POS MV WAVEMASTER II

POS MV WaveMaster II is a user-friendly, turnkey system designed and built to provide accurate attitude, heading, heave, position, and velocity data of your marine vessel and onboard sensors. POS MV is proven in all conditions, and is the georeferencing and motion compensation solution of choice for the hydrographic professional.

POS MV blends GNSS data with angular rate and acceleration data from an IMU and heading from the GPS Azimuth Measurement System (GAMS) to produce a robust and accurate full six degrees-of-freedom position and orientation solution.



PERFORMANCE SUMMARY - POS MV WAVEMASTER II ACCURACY¹

	DGPS	Fugro Marinestar®	IARTK	POSPac MMS PPP	POSPac MMS IAPPK	During GNSS Outage
Positioning	0.5 - 2 m ²	Horizontal: 10 cm 95% Vertical: 15 cm 95%	Horizontal: +/- (8 mm + 1 ppm x baseline length) ³ Vertical: +/- (15 mm + 1 ppm x baseline length) ³	Horizontal: < 0.1 m Vertical: < 0.2 m	Horizontal: +/- (8 mm + 1 ppm x baseline length) ³ Vertical: +/- (15 mm + 1 ppm x baseline length) ³	~ 9 m for 60 s outage(RTK) ~ 3 m for 30 s outage(RTK) ~ 2 m for 60 s outage(IAPPK)
Roll & Pitch ⁴	0.03°	0.02°	0.02°	< 0.02°	0.015°	0.04°
Heading ⁴	0.015° with 4 m baseline 0.03° with 2 m baseline	-	-	-	-	< 2° per hour degradation (negligible for outages <60 s)
Heave TrueHeave™	5 cm or 5% ⁵ 2 cm or 2% ⁶	-	-	-	-	5 cm or 5% ⁵ 2 cm or 2% ⁶

PCS OPTIONS

COMPONENT	DIMENSIONS	WEIGHT	TEMPERATURE	HUMIDITY	POWER
Rack Mount PCS	L = 442 mm, W = 356 mm, H = 46 mm	3.9 kg	-20 °C to +70 °C	10 - 80% RH	AC 120/230 V, 50/60 Hz, auto-switching 40 W
Small Form Factor PCS	L = 167 mm, W = 185 mm, H = 68 mm	2.5 kg	-20 °C to +60 °C	0- 100% RH	DC 10-34 V, 35 W (peak)

INERTIAL MEASUREMENT UNIT (IMU)

ENCLOSURE	DIMENSIONS	WEIGHT	TEMPERATURE	IP RATING
Between Decks	L = 158 mm, W = 158 mm, H = 124 mm	2.5 kg	-40 °C to +60 °C	IP65
Submersible	Ø100 mm (base plate Ø132 mm) X 104 mm ⁷	2.7 kg	-40 °C to +60 °C	IP68

GLOBAL NAVIGATION SATELLITE SYSTEM (GNSS)

COMPONENT	DIMENSIONS	WEIGHT	TEMPERATURE	HUMIDITY
GNSS Antenna	Ø178 mm, W = 73 mm	0.45 kg	-50 °C to +70 °C	0-100% RH

¹ 1 sigma unless otherwise stated

² Depending on quality of differential corrections

³ Assumes 1 m IMU-GNSS antenna offset

⁴ No range limit

⁵ Whichever is greater, for periods of 20 seconds or less

⁶ Whichever is greater, for periods of 35 seconds or less

⁷ Height excludes connector

1. ETHERNET INPUT OUTPUT

Ethernet	(10/100 base-T)
Parameters	Time tag, status, position, attitude, heave, velocity, track and speed, dynamics, performance metrics, raw IMU data, raw GNSS data
Display Port	Low rate (1 Hz) UDP protocol output
Control Port	TCP/IP input for system commands
Primary Port	Real-time (up to 200 Hz) UDP protocol output
Secondary Port	Buffered TCP/IP protocol output for data logging to external device

2. SERIAL RS232 INPUT OUTPUT

5 COM Ports User assignable to: NMEA output (0-5), Binary output (0-5), Auxiliary GNSS input (0-2), Base GNSS correction input (0-2)

3. NMEA ASCII OUTPUT

Parameters	NMEA Standard ASCII messages: Position (\$INGGA), Heading (\$INHDT), Track and Speed (\$INVTG), Statistics (\$INGST), Attitude (\$PASHR, \$PRDID), Time and Date (\$INZDA, \$UTC)
Rate	Up to 50 Hz (user selectable)
Configuration	Output selections and rate individually configurable on each assigned com port

4. HIGH RATE ATTITUDE OUTPUT

Parameters	User selectable binary messages: attitude, heading, speed
Rate	Up to 200 Hz (user selectable)
Configuration	Output selections and rate individually configurable on each assigned com port

5. AUXILIARY GNSS INPUTS

Parameters	NMEA Standard ASCII messages: \$GPGGA, \$GPGST, \$GPGSA, \$GPGSV
Uses Aux input with best quality	
Rate	1 Hz

6. BASE GNSS CORRECTION INPUTS

Parameters	RTCM V2.x, RTCM V3.x, CMR and CMR+, CMRx input formats accepted. Combined with raw GNSS observables in navigation solution
Rate	1 Hz

7. DIGITAL I/O

1PPS	1 pulse-per-second Time Sync output, normally high, active low pulse
Event Input (2)	Time mark of external events. TTL pulses > 1 msec width, rising or falling edge, max rate 200 Hz

8. USER SUPPLIED EQUIPMENT

- PC for POSView Software (Required for configuration): Pentium 90 processor (minimum), 16 MB RAM, 1 MB free disk space, Ethernet adapter (RJ45 100 base T), Windows 7 or Windows 8
- PC for POSpac MMS Post-processing Software: Pentium III 800Mhz or equivalent (minimum), 512 MB RAM, 400 MB free disk space, USB Port (for Security Key if specified, not required for network license), Windows 7 or Windows 8

Scan the QR Code on your mobile device to access information on POS MV



Headquarters: 85 Leek Crescent Richmond Hill, ON Canada L4B 3B3 T +1.905.709.4600 F +1.905.709.6027
United Kingdom: Forester's House, Old Racecourse Oswestry UK SY10 7PW T +44 1691 700500
USA: 9633 Zaka Rd, Houston TX USA 77064 T +1.713.936.2990
marine@applanix.com
www.applanix.com



© 2017, Applanix, A Trimble Company. All rights reserved. Applanix and the Applanix logo are trademarks of Applanix Corporation registered with the Canadian Patent and Trademark Office and other countries. POS MV and POSpac are registered trademarks of Applanix Corporation. All other trademarks are the property of their respective owners. Information subject to change without notice. January 2015